

# **SAFETY DATA SHEET**

Creation Date 25-May-2009 Revision Date 26-May-2017 Revision Number 3

1. Identification

Product Name 1-Chlorobutane

Cat No.: AC447020000, AC447020010

Synonyms n-Butyl chloride

Recommended Use Laboratory chemicals.

Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific Acros Organics
One Reagent Lane One Reagent Lane
Fair Lawn, NJ 07410 Fair Lawn, NJ 07410

Tel: (201) 796-7100

**Emergency Telephone Number** 

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Aspiration Toxicity Category 1

Label Elements

### Signal Word

Danger

### **Hazard Statements**

Highly flammable liquid and vapor May be fatal if swallowed and enters airways



Precautionary Statements Prevention

1-Chlorobutane

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

# 3. Composition / information on ingredients

Component	CAS-No	Weight %
1-Chlorobutane	109-69-3	>95

## 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. **Eve Contact** 

Obtain medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Inhalation Move to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs.

Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting. Call a Ingestion

physician or Poison Control Center immediately. If vomiting occurs naturally, have victim

lean forward.

None reasonably foreseeable. Inhalation of high vapor concentrations may cause Most important symptoms/effects

symptoms like headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically Notes to Physician

# 5. Fire-fighting measures

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed **Suitable Extinguishing Media** 

containers exposed to fire with water spray.

**Unsuitable Extinguishing Media** No information available

-12 °C / 10.4 °F **Flash Point** 

Method -No information available

1-Chlorobutane

Autoignition Temperature 245 °C / 473 °F

**Explosion Limits** 

**Upper** 10.1 vol % **Lower** 1.0 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Carbon monoxide (CO) Carbon dioxide (CO2) Hydrogen chloride gas

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

HealthFlammabilityInstabilityPhysical hazards330N/A

### 6. Accidental release measures

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Remove all sources of

ignition. Take precautionary measures against static discharges.

**Environmental Precautions** Should not be released into the environment. Do not flush into surface water or sanitary

sewer system.

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up**Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

# 7. Handling and storage

Handling Wear personal protective equipment. Ensure adequate ventilation. Avoid ingestion and

inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take

precautionary measures against static discharges.

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area.

Keep away from heat and sources of ignition.

# 8. Exposure controls / personal protection

Exposure Guidelines This product does not contain any hazardous materials with occupational exposure

limitsestablished by the region specific regulatory bodies.

**Engineering Measures** Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

1-Chlorobutane

Skin and body protection Long sleeved clothing.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection** 

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures** 

### 9. Physical and chemical properties

Physical State Liquid **Appearance** Colorless

Odor No information available **Odor Threshold** No information available No information available Hq

-123 °C / -189.4 °F **Melting Point/Range** 

**Boiling Point/Range** 77 - 78 °C / 170.6 - 172.4 °F @ 760 mmHg **Flash Point** -12 °C / 10.4 °F

**Evaporation Rate** No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper 10.1 vol % Lower 1.0 vol %

**Vapor Pressure** 108 mbar @ 20 °C Vapor Density 3.19 (Air = 1.0)**Specific Gravity** 0.880

Solubility No information available Partition coefficient; n-octanol/water No data available **Autoignition Temperature** 245 °C / 473 °F **Decomposition Temperature** No information available **Viscosity** 0.45 mPa.s (20°C)

Molecular Formula C4 H9 CI **Molecular Weight** 92.57

# 10. Stability and reactivity

**Reactive Hazard** None known, based on information available

No information available. Stability

**Conditions to Avoid** Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

**Incompatible Materials** Strong oxidizing agents, Strong bases

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen chloride gas

**Hazardous Polymerization** Hazardous polymerization does not occur.

None under normal processing. **Hazardous Reactions** 

# 11. Toxicological information

**Acute Toxicity** 

See actual entry in RTECS for complete information. **Product Information** 

**Component Information** 

	Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ī	1-Chlorobutane	LD50 = 2670 mg/kg (Rat)	LD50 > 20000 mg/kg (Rabbit)	LC50 > 8000 ppm (Rat) 4 h
- 1				

**Toxicologically Synergistic** No information available

Revision Date 26-May-2017 1-Chlorobutane

#### **Products**

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No information available Irritation Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
1-Chlorobutane	109-69-3	Not listed				

**Mutagenic Effects** Mutagenic effects have occurred in experimental animals.

No information available.

**Reproductive Effects** No information available. **Developmental Effects** No information available.

None known STOT - single exposure STOT - repeated exposure None known Category 1 **Aspiration hazard** 

delayed

**Teratogenicity** 

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

Tumorigenic effects have been reported in experimental animals. Other Adverse Effects

# 12. Ecological information

### **Ecotoxicity**

Do not empty into drains. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
1-Chlorobutane	EC50: > 450 mg/L, 72h	LC50: = 600 mg/L, 48h static	EC50 = 485 mg/L 5 min	EC50: = 3020 mg/L, 48h
	(Desmodesmus	(Leuciscus idus)	EC50 = 732 mg/L 30 min	Static (Daphnia magna)
	subspicatus)		_	EC50: = 452 mg/L, 48h
				(Daphnia magna)
				EC50: = 16 mg/L, 21d
				(Daphnia magna)

Persistence is unlikely based on information available. Persistence and Degradability

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
1-Chlorobutane	2.66

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

## 14. Transport information

DOT

#### 1-Chlorobutane

**UN-No** UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3 Packing Group II

**TDG** 

**UN-No** UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3
Packing Group ||

IA<u>TA</u>

UN-No UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3
Packing Group

IMDG/IMO

UN-No UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3
Packing Group ||

# 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
1-Chlorobutane	Х	Χ	-	203-696-6	-		Χ	Χ	Χ	Χ	Χ

### Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

### 1-Chlorobutane

Not applicable

### **CERCLA**

Not applicable

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals

### U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
1-Chlorobutane	X	X	X	-	-

### **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

### Other International Regulations

Mexico - Grade Serious risk, Grade 3

|--|

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 25-May-2009

 Revision Date
 26-May-2017

 Print Date
 26-May-2017

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**