

# **SAFETY DATA SHEET**

Creation Date 24-Apr-2009 Revision Date 26-May-2017 Revision Number 5

1. Identification

Product Name Ethanol, 200 proof

Cat No.: AC615090000; AC615090010; AC615090020; AC615090040;

AC615091000; AC615095000; NC0549167

**Synonyms** Ethyl alcohol; Absolute ethanol

**Recommended Use**Laboratory chemicals.

Uses advised against

Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410 Fair Lawn, NJ 07410

Tel: (201) 796-7100

**Emergency Telephone Number** 

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

## Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Serious Eye Damage/Eye Irritation Category 2

Label Elements

Signal Word

Danger

**Hazard Statements** 

Highly flammable liquid and vapor Causes serious eye irritation



Ethanol, 200 proof

### **Precautionary Statements**

#### Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

### Response

IF exposed or concerned: Get medical attention/advice

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

### **Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

None identified

# 3. Composition / information on ingredients

Component	CAS-No	Weight %
Ethyl alcohol	64-17-5	99-100

# 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

**Eye Contact**Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Inhalation Move to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms/effects None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting

**Notes to Physician** Treat symptomatically

5. Fire-fighting measures

**Suitable Extinguishing Media** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed

containers exposed to fire with water spray.

**Unsuitable Extinguishing Media** Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire

**Flash Point** 13 °C / 55.4 °F

Method -No information available

363 °C / 685.4 °F **Autoignition Temperature** 

**Explosion Limits** 

Upper 19 vol % Lower 3.3 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Carbon monoxide (CO) Carbon dioxide (CO2)

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	1	N/A

# 6. Accidental release measures

Use personal protective equipment, Ensure adequate ventilation, Remove all sources of **Personal Precautions** 

ignition. Take precautionary measures against static discharges.

Should not be released into the environment. Do not flush into surface water or sanitary **Environmental Precautions** 

sewer system.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Up

Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Ensure Handling adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot

surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take

precautionary measures against static discharges.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from Storage

open flames, hot surfaces and sources of ignition. Flammables area. Keep away from heat

and sources of ignition.

### 8. Exposure controls / personal protection

**Exposure Guidelines** 

Ethanol, 200 proof

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm	IDLH: 3300 ppm	TWA: 1000 ppm
		(Vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>
		TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>	
		TWA: 1900 mg/m <sup>3</sup>	_	

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

**Eye/face Protection**Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Long sleeved clothing.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

No information available

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical State Liquid

Appearance Clear, Colorless

**Odor** Alcohol

Odor ThresholdNo information availablepH7 @ 20°C 10g/l aq.sol

 Melting Point/Range
 -114 °C / -173.2 °F

 Boiling Point/Range
 78 °C / 172.4 °F

 Flash Point
 13 °C / 55.4 °F

Flammability (solid,gas) Not applicable

Flammability or explosive limits

**Evaporation Rate** 

 Upper
 19 vol %

 Lower
 3.3 vol %

Vapor PressureNo information availableVapor DensityNo information availableSpecific Gravity0.785 g/cm3 @20°C

**Solubility** miscible

Partition coefficient; n-octanol/water

Autoignition Temperature

Decomposition Temperature

Viscosity

No data available
363 °C / 685.4 °F
No information available
No information available

Molecular Formula C2 H6 O
Molecular Weight 46.07

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

Ethanol, 200 proof

Stability Hygroscopic.

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot **Conditions to Avoid** 

surfaces and sources of ignition.

Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides **Incompatible Materials** 

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

# 11. Toxicological information

### **Acute Toxicity**

### **Product Information**

**Component Information** 

Component LD50 Oral		LD50 Dermal	LC50 Inhalation		
	Ethyl alcohol	3450 mg/kg ( Mouse )	Not listed	20000 ppm/10H ( Rat )	

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico		
Ethyl alcohol	64-17-5	Group 1	Known	A3	X	Not listed		
IARC: (Internation	nal Agency for Rese	arch on Cancer)	IARC: (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans					
NTP: (National To	oxicity Program)		NTP: (Natio Known - Kr	NTP: (National Toxicity Program) Known - Known Carcinogen				
ACGIH: (America Hygienists)	an Conference of Go	vernmental Industr	Carcinogen ial A1 - Known A2 - Suspe A3 - Anima	Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen al A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen				
OSHA: (Occupation	onal Safety & Health	Administration)		merican Conference cupational Safety & F				

X - Present

Mexico - Occupational Exposure Limits - Carcinogens Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen A5 - Not Suspected as a Human Carcinogen

**Mutagenic Effects** No information available

**Reproductive Effects** No information available. **Developmental Effects** No information available. **Teratogenicity** No information available.

None known STOT - single exposure STOT - repeated exposure None known

Ethanol, 200 proof

**Aspiration hazard** No information available

delayed

Symptoms / effects.both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

The toxicological properties have not been fully investigated. Other Adverse Effects

# 12. Ecological information

#### **Ecotoxicity**

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Component Freshwater Algae		Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l	Fathead minnow	Photobacterium	EC50 = 9268 mg/L/48h
	(Chlorella vulgaris)	(Pimephales promelas)	phosphoreum:EC50 = 34634	EC50 = 10800  mg/L/24h
		LC50 = 14200 mg/l/96h	mg/L/30 min	
			Photobacterium	
			phosphoreum:EC50 = 35470	
			mg/L/5 min	

Persistence is unlikely based on information available. Persistence and Degradability

**Bioaccumulation/ Accumulation** No information available.

Will likely be mobile in the environment due to its volatility. **Mobility** 

Component	log Pow
Ethyl alcohol	-0.32

## 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

# 14. Transport information

DOT

**UN-No** UN1170 **Proper Shipping Name ETHANOL** 

**Hazard Class** 3 **Packing Group** Ш

**TDG** 

UN-No UN1170 **ETHANOL Proper Shipping Name** 

**Hazard Class** 3 **Packing Group** Ш

**IATA** 

UN1170 **UN-No Proper Shipping Name ETHANOL** 

**Hazard Class** Packing Group Ш

IMDG/IMO

**UN-No** UN1170 **Proper Shipping Name ETHANOL** 

**Hazard Class** 3 **Packing Group** Ш

# 15. Regulatory information

Ethanol, 200 proof

### All of the components in the product are on the following Inventory lists: X = listed

#### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethyl alcohol	Χ	Χ	-	200-578-6	-		Χ	Χ	Χ	Х	Χ

#### Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

Not applicable

CERCLA Not applicable

California Proposition 65 This product contains the following proposition 65 chemicals Ethyl alcohol is only a

considered a Proposition 65 developmental hazard when it is ingested as an alcoholic

beverage

	Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Г	Ethyl alcohol	64-17-5	Development (alcoholic	-	Developmental
	,		beverages only)		Carcinogen

# U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl alcohol	X	X	X	X	X

# **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N

DOT Severe Marine Pollutant N

### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

## Other International Regulations

Mexico - Grade Serious risk, Grade 3

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 24-Apr-2009

 Revision Date
 26-May-2017

 Print Date
 26-May-2017

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS). SDS sections

updated. 2.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**