

SAFETY DATA SHEET

Creation Date 01-Oct-2009

Revision Date 25-Jul-2018

Revision Number 11

1. Identification

Product Name

Gram Crystal Violet

Cat No. :

R40052, R40053, R40073

Synonyms

No information available

Recommended Use Uses advised against Laboratory chemicals. Food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company_

Remel 12076 Santa Fe Drive Lenexa, KS 66215 United States Telephone: 1-800-255-6730 Fax:1-800-621-8251

Emergency Telephone Number

INFOTRAC - 24 Hour Number: 1-800-535-5053 Outside of the United States, call 24 Hour Number: 001-352-323-3500 (Call Collect)

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Carcinogenicity

Category 3 Category 1B

Label Elements

Signal Word Danger

Hazard Statements Flammable liquid and vapor May cause cancer



Precautionary Statements Prevention Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Response

IF exposed or concerned: Get medical attention/advice

Skin IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Phenol	108-95-2	< 1.0
Ethyl alcohol	64-17-5	14
Methyl alcohol	67-56-1	<1.0
Isopropyl alcohol	67-63-0	<1.0
C.I. Basic Violet 3 (with >/= 0.1% Michler's ketone)	548-62-9	<1.0

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately.
Most important symptoms and effects Notes to Physician	None reasonably foreseeable Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.
Unsuitable Extinguishing Media	No information available
Flash Point	38.9 °C / 102 °F
Method -	No information available
Autoignition Temperature Explosion Limits	No information available
Upper	No data available
Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	No data available t No information available No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None known

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA Health 3	Flammability 2	Instability 0	Physical hazards N/A
	6. Accidental re	lease measures	
Personal Precautions	Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.		
Environmental Precautions			
Methods for Containment and Up	-	tion. Use spark-proof tools and	
	7. Handling	and storage	
Handling	Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe vapors or spray mist. Do not ingest. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools Take precautionary measures against static discharges.		
Storage	1 0 ,	and cool place. Keep in propertion of the second seco	, , , , , , , , , , , , , , , , , , , ,
8	. Exposure controls	/ personal protecti	on

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Phenol	TWA: 5 ppm Skin	(Vacated) TWA: 5 ppm (Vacated) TWA: 19 mg/m ³	IDLH: 250 ppm TWA: 5 ppm	TWA: 5 ppm TWA: 19 mg/m ³
		Skin TWA: 5 ppm TWA: 19 ma/m³	TWA: 19 mg/m ³ Ceiling: 15.6 ppm Ceiling: 60 mg/m ³	STEL: 10 ppm STEL: 38 mg/m ³
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m ³ TWA: 1000 ppm TWA: 1900 mg/m ³	IDLH: 3300 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 310 mg/m ³
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³	TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.
Personal Protective Equipment	
Eye/face Protection	Tightly fitting safety goggles.
Skin and body protection	Long sleeved clothing.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. Physical and chemical properties		
Physical State	Liquid	
Appearance	Purple	
Odor	No information available	
Odor Threshold	No information available	
pH	No information available	
Melting Point/Range	No data available	
Boiling Point/Range	No information available	
Flash Point	38.9 °C / 102 °F	
Evaporation Rate	No information available	
Flammability (solid,gas)	Not applicable	
Flammability or explosive limits		
Upper	No data available	
Lower	No data available	
Vapor Pressure	No information available	
•		

Vapor Density Specific Gravity Solubility
Partition coefficient; n-octanol/water Autoignition Temperature
Decomposition Temperature Viscosity VOC Content(%)

No information available No information available No information available No data available No information available No information available No information available 16.9997

10. Stability and reactivity

Reactive Hazard	None known, based on information available	
Stability	Stable under normal conditions.	
Conditions to Avoid	Heating in air. Keep away from open flames, hot surfaces and sources of ignition.	
Incompatible Materials	Strong oxidizing agents	
Hazardous Decomposition Products None under normal use conditions		
Hazardous Polymerization	Hazardous polymerization does not occur.	
Hazardous Reactions	None under normal processing.	

11. Toxicological information

Acute Toxicity

Product Information Oral LD50 Dermal LD50 Vapor LC50 Component Information	Based on ATE data, the cl	assification criteria are not met. A assification criteria are not met. A assification criteria are not met. A	ATE > 2000 mg/kg.
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phenol	LD50 = 317 mg/kg (Rat)	LD50 = 630 mg/kg (Rabbit)	LC50 = 316 mg/m ³ (Rat

Phenol	LD50 = 317 mg/kg (Rat) LD50 = 340 mg/kg (Rat)	LD50 = 630 mg/kg (Rabbit)	LC50 = 316 mg/m³(Rat)4 h
Ethyl alcohol	LD50 = 7060 mg/kg(Rat)	Not listed	20000 ppm/10H (Rat)
Methyl alcohol	Calc. ATE 60 mg/kg LD50 > 1187 – 2769 mg/kg (Rat)	Calc. ATE 60 mg/kg LD50 = 17100 mg/kg(Rabbit)	Calc. ATE 0.6 mg/L (vapours) or 0.5 mg/L (mists) LC50 = 128.2 mg/L (Rat) 4 h
Isopropyl alcohol	5840 mg/kg (Rat)	13900 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat)4 h
C.I. Basic Violet 3 (with >/= 0.1% Michler's ketone)	LD50 = 420 mg/kg(Rat)	Not listed	Not listed

Michier's ketone) No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available	
Sensitization	No information available	
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen. Ethanol has been shown to be carcinogenic in long-term studies only when consumed and abused as an alcoholic beverage. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).	

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico		
Phenol	108-95-2	Not listed	Not listed	Not listed	Not listed	Not listed		
Ethyl alcohol	64-17-5	Group 1	Known	A3	Х	Not listed		
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed		
Isopropyl alcohol	67-63-0	Not listed	Not listed	Not listed	Not listed	Not listed		
C.I. Basic Violet 3	548-62-9	Not listed	Not listed	Not listed	Not listed	Not listed		
(with >/= 0.1%								
Michler's ketone)								
NTP: (National To) ACGIH: (American Hygienists)		Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans NTP: (National Toxicity Program) Known - Known Carcinogen Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen Nernmental Industrial A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen AGGIH: (American Conference of Governmental Industrial Hygienists)						
Mutagenic Effects Reproductive Effect	s	No information available						
Developmental Effe	cts	No information available.						
Teratogenicity		No information available.						
STOT - single expos STOT - repeated exp		None known None known						
Aspiration hazard		No information available						
Symptoms / effects delayed	Symptoms of over	exposure may be	neadache, dizzines	ss, tiredness, nause	ea and vomiting			
Endocrine Disruptor	r Information	No information available						
Other Adverse Effect	ts	The toxicological properties have not been fully investigated.						

12. Ecological information

Ecotoxicity The product contains following substances which are hazardous for the environment. Contains a substance which is:. Very toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Phenol	EC50: 187 - 279 mg/L, 72h static (Desmodesmus subspicatus) EC50: 0.0188 - 0.1044 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 46.42 mg/L, 96h (Pseudokirchneriella subcapitata)	4-7 mg/L LC50 96 h 32 mg/L LC50 96 h	EC50 = 23.28 mg/L 5 min	EC50: 10.2 - 15.5 mg/L, 48h (Daphnia magna) EC50: 4.24 - 10.7 mg/L, 48h Static (Daphnia magna)
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	LC50 = 14200 mg/l/96h	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	C C
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h

		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	
			EC50 = 43000 mg/L 5 min	
Isopropyl alcohol	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus)	LC50: = 11130 mg/L, 96h static (Pimephales promelas)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h
	EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas)		

Persistence and Degradability

No information available

Bioaccumulation/Accumulation

No information available.

.

Mobility

Component	log Pow
Phenol	1.5
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Isopropyl alcohol	0.05

13. Disposal considerations

Waste Disposal Methods

Should not be released into the environment.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Phenol - 108-95-2	U188	-
Methyl alcohol - 67-56-1	U154	-

14. Transport information									
DOT									
UN-No	1170								
Proper Shipping Name	AQUEOUS ALCOHOL SOLUTION: NOT REGULATED BY CONFORMING TO 49CFR 173.150(E)								
Hazard Class	3								
Packing Group									
TDG									
UN-No	UN1170								
Proper Shipping Name	ETHANOL SOLUTION								
Hazard Class	3								
Packing Group									
IATA									
UN-No	UN1170								
Proper Shipping Name	ETHANOL SOLUTION								
Hazard Class	3								
Packing Group									
IMDG/IMO									
UN-No	UN1170								
Proper Shipping Name	ETHANOL SOLUTION								
Hazard Class	3								
Packing Group									
	15. Regulatory information								

All of the components in the product are on the following Inventory lists: X = listed

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Phenol	Х	Х	-	203-632-7	-		Х	Х	Х	Х	Х

Ethyl alcohol	Х	Х	-	200-578-6	-	Х	Х	Х	Х	Х
Methyl alcohol	Х	Х	-	200-659-6	-	Х	Х	Х	Х	Х
Isopropyl alcohol	Х	Х	-	200-661-7	-	Х	Х	Х	Х	Х
C.I. Basic Violet 3 (with >/=	Х	Х	-	208-953-6	-	Х	Х	Х	Х	Х
0.1% Michler's ketone)										

Legend: X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Phenol	108-95-2	< 1.0	1.0
Methyl alcohol	67-56-1	<1.0	1.0
Isopropyl alcohol	67-63-0	<1.0	1.0

SARA 311/312 Hazard Categories	See section 2 for more information
--------------------------------	------------------------------------

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Phenol	Х	1000 lb	Х	Х

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Phenol	Х		-
Methyl alcohol	Х		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component		Hazardous Substances RQs	CERCLA EHS RQs
Phenol		1000 lb	1000 lb
Methyl alcohol		5000 lb	-
California Proposition 65	This product	contains the following proposition 65 ch	emicals

California Proposition 65 This product contains the following proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic	-	Developmental
2		beverages only)		Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Phenol	Х	Х	Х	Х	Х
Ethyl alcohol	Х	Х	Х	Х	Х
Methyl alcohol	Х	Х	Х	Х	Х
Isopropyl alcohol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Moderate risk, Grade 2

16. Other information		
Prepared By	Regulatory Affairs	
	Remel	
	Tel: 1-800-255-6730	
Creation Date	01-Oct-2009	
Revision Date	25-Jul-2018	
Print Date	25-Jul-2018	
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).	

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS