

Revision Number: 003.0

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:LoctiteProduct type:SealantRestriction of Use:None idCompany address:Henkel CorporationOne Henkel WayRocky Hill, Connecticut 06067

Loctite All Purpose 2in1 Seal & Bond Sealant None identified IDH number:


1878880

Region:United StatesContact information:Telephone: (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

#### 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW	
DANGER:	CAUSES SERIOUS EYE IRRITATION.	
	MAY DAMAGE FERTILITY OR THE UNBORN CHILD.	
	MAY CAUSE DAMAGE TO ORGANS.	

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
REPRODUCTIVE TOXICITY	1B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	2



#### **Precautionary Statements**

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, clothing, eye and face protection.
Response:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Call a POISON CENTER/doctor/ IF exposed or concerned: Get medical attention. If eye irritation persists: Get medical attention.
Storage:	Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS Hazardous Component(s) CAS Number Percentage\*

IDH number: 1878880

Product name: Loctite All Purpose 2in1 Seal & Bond

Limestone	1317-65-3	20 - 30
Ethylene glycol	107-21-1	1 - 5
Titanium dioxide	13463-67-7	1 - 5
n-Butyl acetate	123-86-4	0.1 - 1
Quartz (SiO2)	14808-60-7	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES				
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.			
Skin contact:	Wash affected area immediately with soap and water. If symptoms develop and persist, get medical attention.			
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.			
Ingestion:	Rinse out mouth. Do not drink. Never give anything by mouth to an unconscious person. If adverse health effects develop seek medical attention			
Symptoms:	See Section 11.			
5. FIRE FIGHTING MEASURES				
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.			
Special firefighting procedures:	Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool.			
Unusual fire or explosion hazards:	This product is an aqueous mixture which will not burn. If evaporated to dryness, the solid residue may pose a slight fire hazard.			
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.			

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Ventilate area. Do not allow product to enter sewer or waterways.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Wear appropriate protective equipment and clothing during clean-up. Dispose of according to Federal, State and local governmental regulations.

#### HANDLING AND STORAGE 7.

Handling:

Avoid contact with eyes. Avoid prolonged or repeated skin contact with this material. Use only with adequate ventilation. Wash hands before breaks and immediately after handling the product. Keep out of the reach of children.

Storage:

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

Keep from freezing.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Limestone10 mg/m3 TWA Total dust.5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.Ethylene glycol25 ppm TWA Vapor fraction 50 ppm STEL Vapor fraction 10 mg/m3 STEL Aerosol, inhalable.NoneTitanium dioxide15 mg/m3 PEL Total dust.15 mg/m3 PEL Total dust.Titanium dioxide10 mg/m3 TWA15 mg/m3 PEL Total dust.n-Butyl acetate50 ppm TWA 150 ppm STEL150 ppm (710 mg/m3) PEL	None	None
Ethylene glycol       fraction 50 ppm STEL Vapor fraction 10 mg/m3 STEL Aerosol, inhalable.       None         Titanium dioxide       15 mg/m3 PEL Total dust.       15 MPPCF TWA Respirable fraction.         110 mg/m3 TWA       15 mg/m3 TWA Total dust.       15 mPCF TWA Respirable fraction.         15 mg/m3 TWA Total dust.       10 mg/m3 TWA       15 mg/m3 TWA Total dust.         10 mg/m3 TWA       50 MPPCF TWA Respirable fraction.       15 mg/m3 TWA         15 mg/m3 TWA       50 MPPCF TWA Total dust.       50 mg/m3 TWA         15 mg/m3 TWA       50 mg/m3 TWA       7 total dust.         15 mg/m3 TWA       5 mg/m3 TWA       7 total dust.         15 mg/m3 TWA       150 ppm (710       10 total dust.		None
Titanium dioxide 10 mg/m3 TWA dust. 10 mg/m3 TWA 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA		
n Butul asstata 50 ppm TWA 150 ppm (710	None	None
	None	None
Quartz (SiO2) Quartz	None	None

**Respiratory protection:** 

Eye/face protection:

Skin protection:

product.

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Safety goggles or safety glasses with side shields.

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

#### PHYSICAL AND CHEMICAL PROPERTIES 9.

Solid

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density:

White Acetate Not available. 6.5 - 7.5 17.5 mbar (20 °C (68°F)) no method > 100 °C (> 212°F) Not available. 1.3 Heavier than air, (Air = 1)

Product name: Loctite All Purpose 2in1 Seal & Bond

Flash point:	This product does not sustain combustion (ASTM D4206).
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	0.3 (Butyl acetate = 1)
Solubility in water:	Soluble
Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature:	Not available. 1.14 %; 142 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) 360,000 - 520,000 cp Not available.

## **10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	This product may react with strong acids, bases and oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

## **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure:

Skin, Inhalation

#### Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors from uncured sealant may cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz,
	a cancer hazard by inhalation. Normal use of this product causes no such release.
Skin contact:	Prolonged or repeated contact with uncured sealant may cause skin irritation.
Eye contact:	May cause irritation.
Ingestion:	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Ethylene glycol	Oral LD50 (Rat) = 5.89 g/kg Oral LD50 (Mouse) = 14.6 g/kg Dermal LD50 (Rabbit) = 9,530 mg/kg	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
n-Butyl acetate	Oral LD50 (Rat) = 14,000 mg/kg Oral LD50 (Rat) = 14,130 mg/kg	Irritant, Central nervous system
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Ethylene glycol	No	No	No
Titanium dioxide	No	Group 2B	No
n-Butyl acetate	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	Yes

#### 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Not available.

### **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

Dispose of according to Federal, State and local governmental regulations.

It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

#### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

#### **15. REGULATORY INFORMATION**

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act	
TSCA 12 (b) Export Notification:	Inventory. None above reporting de minimis	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1).	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.	
16. OTHER INFORMATION		

# This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes

from the previous version in Section(s): 2, 9, 16

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/22/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.