

McKESSON

SDS DATE: 8/7/2015

SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: McKesson Isopropyl Rubbing Alcohol 70%
MFR #: 23-D0022, 23-D0024

DISTRIBUTED BY: McKesson Medical-Surgical Inc.
9954 Mayland Drive, Suite 4000
Richmond, Virginia 23233

INFORMATION LINE: 1-800-777-4908
Monday – Friday 8:00 a.m. – 6:00 p.m. EST

EMERGENCY PHONE: 1-800-451-8346 (3E Company)
Day or night

PRODUCT DESCRIPTION: Alcohol, Isopropyl 70%

SECTION 2: HAZARDS IDENTIFICATION

ROUTES OF ENTRY: N/A

POTENTIAL HEALTH EFFECTS: N/A

EYES: N/A

SKIN: N/A

INGESTION: N/A

INHALATION: N/A

ACUTE HEALTH HAZARDS: N/A

CHRONIC HEALTH HAZARDS: N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

CARCINOGENICITY

OSHA: No

ACGIH: N/A

NTP: No

IARC: Group 1: No, Group 2a: No, Group 2b: No, Group 3: Yes, Group 4: No

OTHER: N/A

SECTION 2 NOTES:

Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.

Eye Irrit. 2;H319 Causes serious eye irritation.

STOT SE 3;H336 May cause drowsiness or dizziness.

Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Warning

H226 Flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness and dizziness.

Prevention

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
 P235 Keep cool.
 P240 Ground / bond container and receiving equipment.
 P241 Use explosion-proof electrical / ventilating / light / equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves / eye protection / face protection.

Response

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
 P337+313 If eye irritation persists: Get medical advice / attention.
 P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

Storage

P403+233 Store in a well ventilated place. Keep container tightly closed.
 P405 Store locked up.

Disposal

P501 Dispose of contents / container in accordance with local / national regulations.

SECTION 3: COMPOSITION/INFORMATION OF INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>%</u>	<u>Exposure Limits</u>
Isopropyl Alcohol	67-63-0	50-75	OSHA TWA 400 ppm (980mg/m3) STEL 500 ppm ACGIH TWA: 200 ppm STEL: 400 ppm Revised 2003, NIOSH TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3)

SECTION 3 NOTES:

GHS Classification:
 Flam. Liq. 2;H225
 Eye Irrit. 2;H319
 STOT SE 3;H336

Substance classified with a health or environmental hazard.

MCKESSON

SDS DATE: 8/7/2015

Substance with a workplace exposure limit.
PBT-substance or vPvB-substance.

SECTION 4: FIRST-AID MEASURES

EYES: Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

SKIN: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

INGESTION: If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

INHALATION: Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 4 NOTES: N

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Overview Signs and Symptoms of Exposure: Giddiness, headache, dizziness and nausea.

Medical Conditions Generally Aggravated by Exposure: Pre-existing and respiratory disorders, may be aggravated by exposure.

Health Hazards (Acute and Chronic): Generally used as a rubdown. Vapor irritates eyes.

High concentration of vapor can irritate respiratory tract, is anesthetic and may cause CNS depression.

Not a carcinogen.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation May cause drowsiness or dizziness.

Eyes Causes serious eye irritation.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: 12
(% BY VOLUME) **LOWER:** 2

FLASH POINT: 77 F
METHOD USED: TCC

AUTOIGNITION TEMPERATURE: N/A

NFPA HAZARD CLASSIFICATION

HEALTH:	N/A	FLAMMABILITY:	N/A	REACTIVITY:	N/A	OTHER:	N/A
----------------	-----	----------------------	-----	--------------------	-----	---------------	-----

HMIS HAZARD CLASSIFICATION

MCKESSON

HEALTH: N/A

FLAMMABILITY: N/A

REACTIVITY: N/A

SDS DATE: 8/7/2015
PERSONAL: N/A

EXTINGUISHING MEDIA:

Recommended extinguishing media; alcohol resistant foam, CO₂, water fog.

Do not use; water jet.

SPECIAL FIRE FIGHTING PROCEDURES:

UNUSUAL FIRE AND EXPLOSION HAZARDS:

HAZARDOUS DECOMPOSITION PRODUCTS:

SECTION 5 NOTES:

Special hazards arising from the substance or mixture

Hazardous decomposition: Burning may produce carbon monoxide and carbon dioxide contamination.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Advice for fire-fighters

Dilution of burning liquid with water will affect extinguishment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:

SECTION 6 NOTES:

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Environmental precautions

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Methods and material for containment and cleaning up

Eliminate all sources of ignition. Small spills should be flushed with large quantities of water, larger spills should be collected for disposal. Atomize into an incinerator where permitted under appropriate federal, state, and local regulations.

SECTION 7: HANDLING AND STORAGE

HANDLING: Do NOT take internally. Flammable liquid. Keep away from heat, sparks and open flames. Keep container closed.

STORAGE: Handle containers carefully to prevent damage and spillage. Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard. Incompatible materials: Anyhydride, isocyanate, monomer and organo-metallic.

OTHER PRECAUTIONS: N/A

SECTION 7 NOTES: N/A

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

VENTILATION:

MCKESSON

SDS DATE: 8/7/2015

RESPIRATORY PROTECTION: If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

EYE PROTECTION: Protective goggles if desired.

SKIN PROTECTION: Rubber or vinyl gloves if desired.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N/A

WORK HYGIENIC PRACTICES:

Ensure showers and eyewash stations are available. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

EXPOSURE GUIDELINES: N/A

SECTION 8 NOTES:

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR: Colorless Liquid, Characteristic

PHYSICAL STATE:

pH AS SUPPLIED: Not Measured

pH (Other): N/A

BOILING POINT: 87°F

MELTING POINT: Not Measured

FREEZING POINT: Not Measured

VAPOR PRESSURE (mmHg): 33

@ N/A

DENSITY (lb/gal): 2.07

@ N/A

SPECIFIC GRAVITY (H₂O = 1): 0.88

@ N/A

EVAPORATION RATE: 2.3

BASIS (=1): N/A

SOLUBILITY IN WATER: Complete

PERCENT SOLIDS BY WEIGHT: N/A

PERCENT VOLATILE: N/A

BY WT/ N/A BY VOL @ N/A

VOLATILE ORGANIC COMPOUNDS (VOC): N/A

WITH WATER: N/A LBS/GAL

WITHOUT WATER: N/A LBS/GAL

MOLECULAR WEIGHT: N/A

VISCOSITY: Not Measured

SECTION 9 NOTES: N/A

SECTION 10: STABILITY AND REACTIVITY

STABLE

UNSTABLE

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID (STABILITY): Avoid heat, sparks and open flame.

INCOMPATIBILITY (MATERIAL TO AVOID): Anhydride, isocyanate, monomer and organo-metallic

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Burning may product carbon monoxide and carbon dioxide contamination.

HAZARDOUS POLYMERIZATION: N/A

CONDITIONS TO AVOID (POLYMERIZATION): N/A

SECTION 10 NOTES:

Reactivity

Hazardous Polymerization will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Acute toxicity

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient Isopropyl Alcohol (67-63-0)

Oral LD50 mg/kg , 4,710.00, Rat – Category 5
Skin LD50 mg/kg, 12,800.00, Rat – Category N/A
Inhalation Vapor mg/l/4hr, 72.60, Rat – Category N/A
Inhalation Dust/Mist LD50 mg/l/4h – No data available
Inhalation Gas LD50 ppm – No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification Category Hazard Description

Acute toxicity (oral) --- Not Applicable
Acute toxicity (dermal) --- Not Applicable
Acute toxicity (inhalation) --- Not Applicable
Skin corrosion/irritation --- Not Applicable
Serious eye damage/irritation 2 Causes serious eye irritation.
Respiratory sensitization --- Not Applicable
Skin sensitization --- Not Applicable
Germ cell mutagenicity --- Not Applicable
Carcinogenicity --- Not Applicable
Reproductive toxicity --- Not Applicable
STOT-single exposure 3 May cause drowsiness or dizziness.
STOT-repeated exposure --- Not Applicable
Aspiration hazard --- Not Applicable

SECTION 11 NOTES:

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment.

Ingredient Isopropyl Alcohol (67-63-0)

96 hr LC50Fish, mg/l, 1400.00 *Lepomis macrochirus*
48 hr EC50 crustacea, mg/l , 100.00 *Daphnia magna*
ErC50 algae mg/l, 100.00 (72 hr) *Soenedesmus subspicatus*

SECTION 12 NOTES:

Persistence and degradability: There is no data available on the preparation itself.

Bioaccumulative potential: Not Measured

Mobility in soil: No data available.

Results of PBT and vPvB assessment: This product contains no PBT/vPvB chemicals.
Other adverse effects: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Observe all federal, state and local regulations when disposing of this product.

RCRA HAZARD CLASS: N/A

SECTION 13 NOTES: N/A

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: ISOPROPANOL

HAZARD CLASS: N/A

DOT SHIPPING ID NUMBER: UN 1219

DOT PACKING GROUP: II

DOT HAZARD CLASS: 3

DOT LABEL STATEMENT: N/A

WATER TRANSPORTATION

PROPER SHIPPING NAME: ISOPROPANOL

HAZARD CLASS: 3

ID NUMBER: UN 1219

PACKING GROUP: II

LABEL STATEMENTS: N/A

AIR TRANSPORTATION

PROPER SHIPPING NAME: ISOPROPANOL

HAZARD CLASS: 3

ID NUMBER: UN 1219

PACKING GROUP: II

LABEL STATEMENTS: N/A

SECTION 14 NOTES: EMS-No: F-E, S-D

Small quantity Exception: 49CFR173.4

Exemption for US Ground Transportation: Limited Quantity

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): All components of this material are either listed or exempt from listing on the TSCA inventory.

CECLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): N/A

SARA 311/312 HAZARD CATEGORIES: No chemicals at levels which require reporting under this statute.

SARA 313 REPORTABLE INGREDIENTS: Isopropyl Alcohol

STATE REGULATIONS:

Proposition 65 - Carcinogens (>0.0%):

No chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

No chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

No chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

No chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Isopropyl Alcohol

Pennsylvania RTK Substances (>1%):

Isopropyl Alcohol

MCKESSON

SDS DATE: 8/7/2015

INTERNATIONAL REGULATIONS: WHMIS: B2 D2B

SECTION 15 NOTES:

EPCRA 302 Extremely Hazardous: No chemicals at levels which require reporting under this statute.

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: N/A

PREPARATION INFORMATION: N/A

DISCLAIMER: This information relates onto to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information and recommendations contained herein are to the best of the manufacturer's knowledge and belief accurate and reliable as of the date indicated. No representation warranty or guarantee, however, is made with regards to accuracy, reliability or completeness. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to satisfy itself as to the suitability and completeness of such information for its own particular use. Appropriate warnings and safe-handling procedures should be provided to handlers and users.