

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Goof Off Graffiti Remover VOC Spray	
Company Name:	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100
Web site address:	www.wmbarr.com	
Emergency Contact Information:	3E 24 Hour Emergency Contact W.M. Barr Customer Service	(800)451-8346 (800)398-3892
Intended Use:	Removal of paint, marker, crayon, ink, lipstick, nail and shoe polish, and candle wax.	
Product Code:	FG670, FG672, FG672W	
Additional Information	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

2. HAZARDS IDENTIFICATION

- Flammable Aerosols, Category 1**
- Gas Under Pressure, Liquefied gas**
- Skin Corrosion/Irritation, Category 2**
- Serious Eye Damage/Eye Irritation, Category 1**
- Skin Sensitization, Category 1**
- Germ Cell Mutagenicity, Category 1A**
- Toxic To Reproduction, Category 1B**
- Specific Target Organ Toxicity (single exposure), Category 3**
- Aspiration Toxicity, Category 1**
- Simple Asphyxiant**



GHS Signal Word: **Danger**

GHS Hazard Phrases:

- H223: Flammable aerosol.
- H280: Containers gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage.
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.
- H340: May cause genetic defects.
- H360: May damage fertility or the unborn child.

GHS Precaution Phrases:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211: Do not spray on an open flame or any other ignition source.
- P251: Pressurized container: Do not pierce or burn, even after use.
- P261: Avoid breathing gas/mist/vapors/spray.
- P264: Wash hands thoroughly after handling.
- P271: Use only outdoors or in a well-ventilated area.

Goof Off Graffiti Remover VOC Spray

Printed: 09/11/2015
Revision: 09/11/2015
Supersedes Revision: 04/16/2015

GHS Response Phrases:

P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P281: Use personal protective equipment as required.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+313: IF exposed or concerned: Get medical attention/advice.
P310: Immediately call a POISON CENTER or doctor/physician.
P321: Specific treatment see label.
P331: Do NOT induce vomiting.
P332+313: If skin irritation occurs, get medical advice/attention.
P333+313: If skin irritation or rash occurs, seek medical advice/attention.
P362: Take off contaminated clothing and wash before re-use.
P363: Wash contaminated clothing before reuse.

GHS Storage and Disposal Phrases:

P403+233: Store container tightly closed in well-ventilated place.
P405: Store locked up.
P410+403: Protect from sunlight and store in well-ventilated place.
P412: Do not expose to temperatures exceeding 50 °C/122 °F.
P501: Dispose of contents/container according to local, state and federal regulations.

Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL		0
PPE		X



HMIS:

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

INHALATION:

High concentrations may lead to central nervous system effects including, drowsiness, dizziness, nausea, headaches, paralysis, loss of consciousness, and death. High vapor concentrations are irritating to the eyes, nose, throat, and lungs. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal.

EYE CONTACT:

Contact may cause moderate to severe irritation. May cause temporary corneal clouding.

SKIN CONTACT:

Prolonged or repeated contact can result in defatting, redness, drying of the skin which may result in skin irritation and dermatitis, burning sensation, and possible chemical burns to the skin.

INGESTION:

Aspiration hazard. If ingested or vomited, material may enter lungs and produce damage. May produce central nervous system effects, which include dizziness, loss of balance and coordination, nausea, vomiting, unconsciousness, coma and even death.

CHRONIC OVEREXPOSURE EFFECTS:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal.

TARGET ORGANS OR SYSTEM DAMAGE: eye, respiratory system, nervous system, kidneys, blood-related effects

ROUTES OF ENTRY: inhalation, skin , ingestion

Medical Conditions Generally Aggravated By Exposure: Diseases and disorders of the skin, eye, and lungs (asthma-like conditions).

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
67-64-1	Acetone {2-Propanone}	30.0 -60.0 %	AL3150000
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	15.0 -30.0 %	UY5790000
68439-46-3	Alcohol ethoxylate (Alcohols, C9-11, Ethoxylated)	<10.0 %	AZ8100000
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	<15.0 %	NA
NA	(Trade Secret)	< 3.0 %	NA
5989-27-5	d-Limonene	<10.0 %	GW6360000
66455-14-9	Alcohols, C12-13, ethoxylated	< 5.0 %	AZ0881666

Additional Chemical Information Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:
Skin:
 Remove contaminated clothing. Immediately wash skin thoroughly with large amounts of water and mild soap, if available. Seek medical attention if irritation develops or persists.

Eyes:
 Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.

Inhalation:
 Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:
 If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, poison control center, or hospital emergency room immediately. Never give anything by mouth to an unconscious person.

Signs and Symptoms Of Exposure: See Potential Health Effects.

Note to Physician: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIRE FIGHTING MEASURES

Flammability Classification: Level 3 Aerosol

Flash Pt: 0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits: LEL: 1.8% UEL: 9.5%

Autoignition Pt: No data.

Suitable Extinguishing Media: Use carbon dioxide, dry powder, water spray, or foam.

Unsuitable Extinguishing Media: None known.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear. Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from containers that have been exposed to intense heat or flame.

Flammable Properties and Hazards: FLASHPOINT OF LIQUID CONCENTRATE: 0 F
 FLASHPOINT OF PROPELLANT: -138.23 F (closed cup)

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling: Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Precautions To Be Taken in Storing: Store in a cool, dry place. Do not store near flames or at elevated temperatures. Store out of direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	No data.	No data.	No data.
68439-46-3	Alcohol ethoxylate (Alcohols, C9-11, Ethoxylated)	No data.	No data.	No data.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No data.	No data.	No data.
NA	(Trade Secret)	No data.	No data.	No data.
5989-27-5	d-Limonene	No data.	No data.	No data.
66455-14-9	Alcohols, C12-13, ethoxylated	No data.	No data.	No data.

Respiratory Equipment (Specify Type): For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

Eye Protection: Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.

Protective Gloves: Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.): Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

Work/Hygienic/Maintenance Practices: Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	<input checked="" type="checkbox"/> Gas <input checked="" type="checkbox"/> Liquid <input type="checkbox"/> Solid
Appearance and Odor:	Off-white, opaque.
Melting Point:	No data.
Boiling Point:	No data.
Autoignition Pt:	No data.
Flash Pt:	0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: 1.8% UEL: 9.5%
Specific Gravity (Water = 1):	0.89
Density:	7.423 LB/GL
Vapor Pressure (vs. Air or mm Hg):	No data.
Vapor Density (vs. Air = 1):	> 1
Evaporation Rate:	> 1
Solubility in Water:	Soluble
Percent Volatile:	93.0 % by weight.
VOC / Volume:	46.2700 % WT

10. STABILITY AND REACTIVITY

Stability:	Unstable <input type="checkbox"/> Stable <input checked="" type="checkbox"/>
Conditions To Avoid - Instability:	No data available.
Incompatibility - Materials To Avoid:	Strong oxidizers, strong acids, reactive metals (e.g. sodium, calcium, zinc, etc), materials reactive with hydroxyl compounds, copper alloys, alcohols, amines
Hazardous Decomposition or Byproducts:	Carbon monoxide, carbon dioxide, nitrogen oxides, oxides of citrus terpenes, aldehydes, flammable hydrocarbon fragments (e.g. acetylene)
Possibility of Hazardous Reactions:	Will occur <input type="checkbox"/> Will not occur <input checked="" type="checkbox"/>
Conditions To Avoid - Hazardous Reactions:	No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.

CAS# 67-64-1:

Carcinogenicity/Other Information: Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe. Result:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 872-50-4:

Reproductive Effects:, TDLo, Inhalation, Rat, 116.0 PPM, 6 H, multigenerations.

Result:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

- Drug and Chemical Toxicology., Marcel Dekker, 270 Madison Ave., New York, NY 10016, Vol/p/yr: 18,271, 1995

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Moderate.

Result:

Blood:Other hemolysis with or without anemia.

Blood:Other changes.

Biochemical: Metabolism (Intermediary): Other proteins.

- Food and Chemical Toxicology., Pergamon Press Inc., Maxwell House, Fairview Park, Elmsford, NY 10523, Vol/p/yr: 26,475, 1988

CAS# 68439-46-3:

Acute toxicity, LD50, Oral, Rat, 1378. MG/KG.

Result:

Behavioral: Somnolence (general depressed activity).

Behavioral: Ataxia.

Gastrointestinal:Hypermotility, diarrhea.

- Journal of the American College of Toxicology., Mary Ann Liebert, Inc., New York, NY, Vol/p/yr: 10(4),427, 1991

ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	n.a.	n.a.	n.a.	n.a.
68439-46-3	Alcohol ethoxylate (Alcohols, C9-11, Ethoxylated)	n.a.	n.a.	n.a.	n.a.
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	n.a.	n.a.	n.a.	n.a.
NA	(Trade Secret)	n.a.	n.a.	n.a.	n.a.
5989-27-5	d-Limonene	n.a.	3	n.a.	n.a.
66455-14-9	Alcohols, C12-13, ethoxylated	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: No information available for this product as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state, and federal laws.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Consumer Commodity, ORM-D
DOT Hazard Class:
UN/NA Number:

Additional Transport Information:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	No	No	Yes
68439-46-3	Alcohol ethoxylate (Alcohols, C9-11, Ethoxylated)	No	No	No
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No	No	No
NA	(Trade Secret)	No	No	No
5989-27-5	d-Limonene	No	No	No
66455-14-9	Alcohols, C12-13, ethoxylated	No	No	No

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Acute (immediate) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Chronic (delayed) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Fire Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Sudden Release of Pressure Hazard
<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test, 12(b); CA PROP.65: Yes
68439-46-3	Alcohol ethoxylate (Alcohols, C9-11, Ethoxylated)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
NA	(Trade Secret)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
5989-27-5	d-Limonene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
66455-14-9	Alcohols, C12-13, ethoxylated	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

16. OTHER INFORMATION

Revision Date: 09/11/2015
Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.