

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Goof Off Heavy Duty 3% VOC	
Company Name:	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100
Web site address:	www.wmbarr.com	
Emergency Contact:	3E 24 Hour Emergency Contact	(800)451-8346
Information:	W.M. Barr Customer Service	(800)398-3892
Intended Use:	Mult-Purpose Remover for tar, ink, paint, adhesive, etc.	
Synonyms:	FG659, FG659B, FG659BWS, FG701, FG701CS, FG708, FG720, FG748, FG748C, FG659W, FG659BLWS, FG659MT, FG659S, FG732, FG780, FG659BW, FG722	
Additional Information	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

2. HAZARDS IDENTIFICATION

Skin Corrosion/Irritation, Category 2
 Serious Eye Damage/Eye Irritation, Category 2
 Specific Target Organ Toxicity (single exposure), Category 3



GHS Signal Word:	Warning
GHS Hazard Phrases:	H315: Causes skin irritation. H319: Causes serious eye irritation. H335: May cause respiratory irritation.
GHS Precaution Phrases:	P261: Avoid breathing gas/mist/vapors/spray. P264: Wash hands thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection.
GHS Response Phrases:	P302+352: IF ON SKIN: Wash with plenty of soap and water. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P321: Specific treatment see label. P332+313: If skin irritation occurs, get medical advice/attention. P337+313: If eye irritation persists, get medical advice/attention. P362: Take off contaminated clothing and wash before re-use.
GHS Storage and Disposal Phrases:	P403+233: Store container tightly closed in well-ventilated place. P405: Store locked up. P501: Dispose of contents/container according to local, state and federal regulations.

Goof Off Heavy Duty 3% VOC


Printed: 04/16/2015

Revision: 04/16/2015

Supersedes Revision: 04/14/2015

Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL		0
PPE		X



HMIS:

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

This material has not been tested as a whole for health effects. Effects listed are those of the individually listed ingredients in this msds.

Eyes:

May cause severe irritation. May cause moderate corneal injury. Effects may include discomfort or pain, and redness. Effects may be slow to heal.

Skin:

Brief contact may cause slight skin irritation with local redness. Repeated exposure may cause irritation, even a burn. May cause more severe response on covered skin (under clothing, gloves).

Inhalation:

When used as directed, the consumer is not expected to experience any exposure effects. Excessive exposure may cause irritation to the upper respiratory tract. Symptoms may include a headache, dizziness, or nausea.

Ingestion:

Moderately toxic if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury. However, swallowing larger amounts may cause injury.

Target Organs: Blood (Hemolysis), Kidneys, Liver, Eyes, Skin, Central Nervous System.

Primary Routes of Entry: Eyes, Skin, Inhalation, Ingestion

Medical Conditions Generally None known.

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
100-51-6	Benzenemethanol {Benzyl alcohol}	5.0 -10.0 %	DN3150000
143-18-0	Oleic acid potassium salt	5.0 -10.0 %	RK1150000
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	1.0 -5.0 %	KJ8575000
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	1.0 -5.0 %	KJ9100000
770-35-4	Propylene glycol phenyl ether {(not 313)}	1.0 -5.0 %	UB8886500

Additional Chemical Information

Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:	<p>Skin: Remove contaminated clothing. Immediately wash skin thoroughly with large amounts of water and mild soap, if available. Seek medical attention if irritation develops or persists.</p> <p>Eyes: Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.</p> <p>Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.</p> <p>Ingestion: If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.</p>
Signs and Symptoms Of Exposure:	See Potential Health Effects.

5. FIRE FIGHTING MEASURES

Flash Pt:	Not flammable or combustible > 212.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: none UEL: none
Autoignition Pt:	NP
Suitable Extinguishing Media:	Non-combustible liquid - use extinguishing media for underlying cause of fire.
Unsuitable Extinguishing Media:	None known.
Fire Fighting Instructions:	Material is not flammable or combustible. No special fire fighting instructions required.
Flammable Properties and Hazards:	None
Additional Fire Fighting Information	NP = Not applicable

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	Prevent entry into waterways, sewers, or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers for proper disposal. For large spills, dike ahead of the spill.
---	--

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. A source of clean water should be kept in the immediate work area for flushing of the eyes and skin.
Precautions To Be Taken in Storing:	Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Keep containers closed when not in use. Store in a cool, dry place, out of direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
100-51-6	Benzenemethanol (Benzyl alcohol)	No data.	No data.	No data.
143-18-0	Oleic acid potassium salt	No data.	No data.	No data.
111-76-2	Ethanol, 2-Butoxy- (Ethylene glycol n-butyl ether, (a glycol ether))	PEL: 50 ppm	TLV: 20 ppm	No data.
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	No data.	No data.	No data.
770-35-4	Propylene glycol phenyl ether {(not 313)}	No data.	No data.	No data.

Respiratory Equipment (Specify Type):

When used by the consumer following directions for use and with adequate ventilation, respiratory protection is not expected to be needed.

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

If the work area is not properly ventilated to keep airborne levels below their exposure limits, you must use a properly fitted and maintained NIOSH approved respirator for organic vapors. A dust mask does not provide protection against vapors.

Eye Protection:

Where contact with the eyes or face is likely from spraying or splashing, safety glasses, a faceshield or chemical goggles should be worn to prevent eye contact.

Protective Gloves:

When used as directed, protective gloves should not be required. For prolonged or repeated contact, wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as natural rubber or nitrile rubber provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information.

Other Protective Clothing:

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.):

Ventilation is normally not required when handling or using this product to keep exposure to airborne contaminants below the exposure limit.

Good general ventilation should be sufficient to control airborne levels.

Work/Hygienic/Maintenance Practices:

Wash hands thoroughly after use and before eating, drinking, or smoking. Do not eat, drink, or smoke in the work area. Discard any clothing or other protective equipment that cannot be decontaminated.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: Gas Liquid Solid
 Appearance and Odor: Slight yellow to clear, transparent, almond-like odor.
 Melting Point: 32.00 F
 Boiling Point: 212.00 F
 Autoignition Pt: NP
 Flash Pt: > 212.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
 Explosive Limits: LEL: none UEL: none
 Specific Gravity (Water = 1): 0.997
 Density: 8.3 LB/GL
 Vapor Pressure (vs. Air or mm Hg): < 0.1 MM HG
 Vapor Density (vs. Air = 1): > 1
 Evaporation Rate: < 1
 Solubility in Water: Complete
 pH: 8.3 - 8.7
 Percent Volatile: ~ 87 % by weight.
 VOC / Volume: 3.0000 % WT

10. STABILITY AND REACTIVITY

Stability: Unstable Stable
 Conditions To Avoid - stability: None known.
 Incompatibility - Materials To Avoid: Strong oxidizing agents, isocyanates, acetaldehyde, aluminum alkyl compounds and strong mineral acids.
 Hazardous Decomposition Or Byproducts: Carbon monoxide, carbon dioxide
 Possibility of Hazardous Reactions: Will occur Will not occur
 Conditions To Avoid - Hazardous Reactions: None known.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Material has not been tested as a whole. Data is for individual ingredients. Refer to section 2 for acute and chronic effects.

Chronic Toxicological Effects:

CAS# 111-76-2:
 Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.
 Result:
 Behavioral: Ataxia.
 Nutritional and Gross Metabolic: Weight loss or decreased weight gain.
 - Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983

Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.
 Result:
 Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).
 Effects on Embryo or Fetus: Other effects to embryo.
 Specific Developmental Abnormalities: Musculoskeletal system.
 - Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,

Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.
 Result:
 Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.
 Result:
 Effects on Newborn: Apgar score (human only).
 Effects on Newborn: Other neonatal measures or effects.
 Effects on Newborn: Drug dependency.
 - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 112-34-5:
 Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.
 Result:
 Behavioral: Anticonvulsant.
 - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

Carcinogenicity/Other Information: ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans IARC 3: Not Classifiable as to Carcinogenicity in Humans.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
100-51-6	Benzenemethanol {Benzyl alcohol}	n.a.	n.a.	n.a.	n.a.
143-18-0	Oleic acid potassium salt	n.a.	n.a.	n.a.	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	n.a.	3	A3	n.a.
112-34-5	Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	n.a.	n.a.	n.a.	n.a.

770-35-4 Propylene glycol phenyl ether {(not 313)} n.a. n.a. n.a. n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: Not determined for this product as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations. Do not dump into sewers or allow to enter waterways.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated by D.O.T.

DOT Hazard Class:

UN/NA Number:

Additional Transport Information:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
100-51-6	Benzenemethanol (Benzyl alcohol)	No	No	No
143-18-0	Oleic acid potassium salt	No	No	No
111-76-2	Ethanol, 2-Butoxy- (Ethylene glycol n-butyl ether, (a glycol ether))	No	No	Yes-Cat. N230
112-34-5	Diethylene glycol monobutyl ether (2-(2-Butoxyethoxy)ethanol ((a glycol ether))	No	No	Yes-Cat. N230
770-35-4	Propylene glycol phenyl ether {(not 313)}	No	No	No

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Acute (immediate) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Chronic (delayed) Health Hazard
<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Fire Hazard
<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Sudden Release of Pressure Hazard
<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
100-51-6	Benzenemethanol (Benzyl alcohol)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
143-18-0	Oleic acid potassium salt	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
111-76-2	Ethanol, 2-Butoxy- (Ethylene glycol n-butyl ether, (a glycol ether))	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
112-34-5	Diethylene glycol monobutyl ether (2-(2-Butoxyethoxy)ethanol ((a glycol ether))	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
770-35-4	Propylene glycol phenyl ether {(not 313)}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8A PAIR, 8D TERM; CA PROP.65: No

16. OTHER INFORMATION

Revision Date: 04/16/2015

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.